



Shenzhen Fuzhe Technology Co.,Ltd.

Add: C209, Yuanzheng, Bantian, Longgang District, Shenzhen, Guangdong, China. 518129

Tel: +86 755 84528255 Email: kf178@163.com www.fulaser.com

1000-3000mW 980nm Infrared Laser

FEATURES

Miniature size
Collimated straight beam
Adjustable focus
Easy use & maintenance free
Longlife operation
High efficiency
High reliability

APPLICATIONS

Thermal printing
Material Inspection
Scanning Biochemistry
Lidar

Specifications

Model No.	FU980AD1W-F100(1000mW) FU980AD2W-F100(2000mW) FU980AD3W-F100(3000mW)
Wavelength	980(+/-5) nm
Spatial Mode	multimode
Output Power	1000mW, 2000mW, 3000mW
Operation Mode	CW or Modulation
Polarization	10:01
Pointing Stability	<0.05 mrad
Beam Diameter(1/e ²)	6 mm
Beam Divergence	2.5 mrad
Power Stability*	<±3% per 2 hrs
Beam Height	25mm
Temperature Stabilizing	TEC
Warm Up Time	<5 minutes
Beam Quality (M ²)	<2
Optimum Operating	20~30°C
Storage Temperature	10~50°C
MTTF**	10,000 hrs
Laser head dimensions	100(L)x40(W)x50(H)mm3
Power supply	179(W)x148(D)x56(H)mm3 85~265V 50/60Hz input
Modulation	0~30khz Analog or TTL

